ELEPHANT® MEW

HI-LIFT MINE EQUIPMENT WASHER

Chassis:

- > Chassis from well-known chassis supplier (Volvo)
- Tanks in stainless steel, all surfaces are metallized and painted using high quality priming and painting
- > Unique suspension stabilizing system. No outriggers required
- Rear platform for road driving

Color Scheme:

> Chassis cabin, tank section and boom system; white color RAL 9016

High Reach Telescopic Boom System:

- One-man operation enabling driving the unit from basket
- > Open basket to accommodate 1 or 2 persons during operations
- Touch sensors on basket to enable safe maneuvering (optional)
- Fully hydraulic, proportionally controlled work platform with;
 - max. working height of up to 15 meters (approx. 49 feet)
 - max. horizontal outreach of 10 meters, 8 (approx. 33 feet) measured from 1 to 8 meters height
 - max. rated load in basket: 205 kg
- > LED working lights on boom and basket

Tank:

- > 7000 liter water/600 liter detergent tank
- Stainless steel tanks
- > Filling couplings for tanks
- > Onboard refilling solution for detergent

MAJOR ADVANTAGES

- » All-in-one work safe approved unit
- » Hot water high pressure washer
- » High mobility with little set-up time. No outriggers required
- » Ease of use/One-man operation
- » Closer proximity with high reach boom
- » Energy and consumption efficient washer
- » Cameras mounted for improved visibility/safety
- » Multiple pressure guns in basket and at ground level

CERTIFICATIONS

- » CE certified unit
- » ADR registered vehicle
- » Dpt. of Mines & Petroleum Australia Certified





ELEPHANT® MEW

HI-LIFT MINE EQUIPMENT WASHER

Heating & Fluid System:


- > Heat efficient 230 kW diesel heating system
- > Delivers 60 degrees hot water promptly after start
- > Hot water variable operation temperatures up to 95 degrees
- High/low pressure and high/low volume washer system
- > Automatic detergent mix system; 5-20%
- > 3 spray guns in basket and 2 spray guns at the rear platform of the vehicle
 - Two hand-held high-pressure guns able to spray 22 l/min at max. 200 bar (basket/platform)
 - Two hand-held low-pressure guns able to spray 120 l/min at max. 20 bar (basket/platform)
 - Swing arm mounted low-pressure gun able to spray 230 l/min at max. 20 bar (basket)


Control System:

> PLC-based control system, incl. module for trouble-shooting and self-diagnostics

Information Displays:

- > Tank level indications
- > Water temperatures





COMPANY

VESTERGAARD

For questions and requests for further information please contact:

Vestergaard Company A/S

Skullebjerg 31 • Gevninge DK-4000 Roskilde • Denmark Tel: +45 4642 2222 sales@vestergaardcompany.com www.vestergaardcompany.com

Vestergaard Company Inc.

1903 W. Rte. 120 McHenry, IL 60051 • USA Tel: +1 815 759-9102 Toll free: +1 888 759-9118 usa@vestergaardcompany.com

Vestergaard Company SASU

Bâtiment 3450 A, 4, Rue du Té 93290 Tremblay-en-France • France

Tel.: +33 1 30 34 55 87 france@vestergaardcompany.com

Vestergaard Company Ltd.

21/46 Moo 10, Nongkham, Sriracha, Chonburi 20230 • Thailand Tel: +66 33 265769 asia@vestergaardcompany.com